





CORDPLAST[®]

AEROCORD PU/ECO

			
mm	BAR	gr/mt	mm
50	0,2	285	35
60	0,15	255	42
70	0,13	300	55
80	0,1	340	60
90	0,09	380	67
100	0,09	410	75
120	0,07	550	90
125	0,06	565	92
130	0,06	580	95
140	0,05	680	100
150	0,05	765	110
160	0,05	815	120
180	0,04	860	130
200	0,04	955	150
250	0,03	1150	180
300	0,02	1385	220
350	0,02	2030	250



IMPIEGO

Tubo in poliuretano con spirale di acciaio armonico zincato; Idoneo all'aspirazione di polveri abrasive in genere. Particolarmente indicato nelle carrozzerie, nell'industria del legno, ceramica e farmaceutica.



COLORE

Trasparente, spirale zincata.

COMPRESSIBILITA' ASSIALE

8 a 1

NORME

ISO 1307



TEMPERATURA

-40°C / +90°C -40°F / +194°F



LUNGHEZZA

mt 20, mt 10 dal Ø 250

SATI GROUP S.P.A.

Via C. Bonazzi, 24 - 40013 CASTEL MAGGIORE (BO) - ITALY

Tel. +39.051.700321 - Fax +39.051.701350

E-mail: commerciale@satigroup.it

web: www.satigroup.it