

Delta™ Drip

(Registered Design)
Adjustable Drip Emitter



Delta™ Drip 4.5 mm Barb End-Line Delta™ Drip 4.5 mm Barb In-Line

Rotation of the key in the body adjusts the flow rate from 0 to 6 l/h at 100 kPa. Flow rate may be increased or decreased until final shut off.

PRODUCT FEATURES

- Turbulent flow path.
- Two key types available.
 1. End-Line Adjustable 0-6 l/h key. (Black)
 2. In-Line Adjustable 0-6 l/h key. (Brown)
- Two body types to choose from depending on application.
 1. Standard body with 4.5 mm inlet barb.
 2. Spike with 4.5 mm inlet barb.
- Finger tip key control for flow adjustment.
- May be turned "OFF" when not in use.

GENERAL APPLICATIONS

- May be used for vegetable patches, home gardens, nurseries, pots and shrubs.



Delta™ Drip Spike End-Line

Delta™ Drip Spike In-Line

METRIC PERFORMANCE DATA			
DRIPPERS	 Adjustable to 6 lph at 100 kPa	PRESSURE	FLOW
		(bar)	(l/h)
		0.5	0 - 4.1
		0.75	0 - 5.1
		1.0	0 - 6.0
		1.25	0 - 6.8
1.5	0 - 7.5		

Recommended operating pressure 1.0 bar

FILTRATION REQUIREMENTS

- Drip Emitters: 100 microns (150 mesh)



DELTA™ DRIP EMITTERS						PERFORMANCE GRAPHS
PACKAGING						
		BARB End-Line	SPIKE End-Line	BARB In-Line	SPIKE In-Line	
Order Codes	PACKS	200916	200904	203936	203944	
	BULK	020091	020090	020393	020394	
Quantity per Bag	PACKS	100	25	100	25	
	BULK	1000	1500	1000	1250	
Bags per Carton	PACKS	70	50	70	50	
	BULK	7	1	7	1	
Weight per Carton (kg)	PACKS	13.4	7.0	13.4	7.0	
	BULK	13.1	6.8	13.1	6.8	
Base Inlet Connection		4.5 mm Barb	4.5 mm Barb	4.5 mm Barb	4.5 mm Barb	
Dimensions of Assembled	HEIGHT	17 mm	127 mm	17 mm	127 mm	
	WIDTH	51 mm	51 mm	61 mm	61 mm	
	DEPTH	9 mm	10 mm	9 mm	10 mm	
	WEIGHT	1.72 g	4.63 g	1.8 g	4.7 g	
Material UV Stabilized	Body	Polypropylene		Polypropylene		
	Spike		Polypropylene		Polypropylene	