

## Electromechanical control panels

# BASIC 1

RANGE 0,5÷17,5HP

Direct starting electromechanical control panel 1 motor

### GENERAL SPECIFICATIONS

- Operating voltage 400Vac  $\pm 10\%$  50/60Hz
- Start-stop button
- Contactor
- Thermal relay (internal reset)
- External thermoplastic box
- Protection degree IP55
- Operating temperature -5/+40°C

### PROTECTIONS

- Maximum current protection



#### THREE-PHASE 400Vac $\pm 10\%$ 50/60Hz

CODE	TYPE	POWER		OPERATING CURRENT [A]	DIMENSIONS mm			WEIGHT Kg	BOX
		kW	Hp		A-H	L-W	P-D		
SA610.00	BASIC 1 400 0,5	0,37	0,5	0,9÷1,5	184	88	140	0,8	-
SA610.01/02	BASIC 1 400 1	0,55÷0,75	0,75÷1	1,4÷2,3	184	88	140	0,8	-
SA610.03/04	BASIC 1 400 2	1,1÷1,5	1,5÷2	3÷5	184	88	140	0,8	-
SA610.05/06	BASIC 1 400 3	1,8÷2,2	2,5÷3	4,5÷7,5	184	88	140	0,8	-
SA610.07/08	BASIC 1 400 5	3÷3,7	4÷5	6÷10	184	88	140	0,8	-
SA610.09	BASIC 1 400 5,5	4	5,5	9÷15	184	88	140	0,8	-
SA610.10	BASIC 1 400 7,5	5,5	7,5	13÷18	202	88	155	1	-
SA610.11	BASIC 1 400 10	7,5	10	17÷23	234	110	170	1,2	-
SA610.12	BASIC 1 400 12,5	9,2	12,5	20÷25	234	110	170	1,2	-
SA610.13/14	BASIC 1 400 17,5	11÷13	15÷17,5	24÷32	234	110	170	1,3	-