

# BASIC ALARM

Visual and acoustic alarm indicator



## GENERAL SPECIFICATIONS

- Operating voltage 12±24Vac/dc-230Vac
- Visual Led indicator
- Acoustic indicator
- Connection terminal board
- External thermoplastic box
- Cable glands
- Protection degree IP55
- Operating temperature -5/+40°C

## INPUTS / OUTPUTS

- Input for external command

CODE	TYPE	INDICATOR		POWER SUPPLY	DIMENSIONS mm			WEIGHT Kg	BOX
		VISUAL	ACOUSTIC		A-H	L-W	P-D		
SS100.00	BASIC ALARM VA 012	Led	90dB	12Vdc	180	140	110	0,5	02
SS100.01	BASIC ALARM VA 024	Led	90dB	24Vac	180	140	110	0,5	02
SS100.02	BASIC ALARM VA 230	Led	90dB	230Vac	180	140	110	0,5	02
SS100.03	BASIC ALARM V 012	Led	-	12Vdc	180	140	110	0,5	02
SS100.04	BASIC ALARM V 024	Led	-	24Vac	180	140	110	0,5	02
SS100.05	BASIC ALARM V 230	Led	-	230Vac	180	140	110	0,5	02
SS100.06	BASIC ALARM A 012	-	90dB	12Vdc	180	140	80	0,5	01
SS100.07	BASIC ALARM A 024	-	90dB	24Vac	180	140	80	0,5	01
SS100.08	BASIC ALARM A 230	-	90dB	230Vac	180	140	80	0,5	01